



## LXF II-370×125

### 单头仿形铣床 Single Spindle Copy Router

#### [性能特点]

- 用于铝门窗幕墙型材的各类型孔、槽等的铣削加工。
- 本机结构紧凑，造型美观，体积小，型材夹紧和电机启动均采用气压控制。
- 靠模调整更换简单，适应范围广，效率高，可实现连续加工，操作简单安全。

#### [Product Features]

- It is used for processing several types of holes, grooves and water-slots on aluminum and PVC windows & doors or curtain walls.
- It has the features of compact structure, nice design, smart volume and the air pressure controls the starting up of the motor.
- Easy replacement of the copy-routing plate, large useful scope, high efficiency and convenient operation achieve the continuous processing and safety operation.

#### 🕒 技术参数 Technical Parameters

输入电压	Voltage	380V 50Hz
输入功率	Input power	2.2kW
工作气压	Operation air pressure	0.5 ~ 0.8MPa
耗气量	Air consumption	10L/min
仿形范围	Copy-routing range	370 × 125mm
铣刀直径	Milling cutter diameter	φ 5, φ 8
加工型材截面	Profile section	w230 × h150~210mm (depends on the length of the cutter)
机床外形尺寸	Dimension	2180 × 1000 × 1700mm(L × W × H)
变频电主轴	Spindle rational speed	0-12000r/min
重量	Weight	230Kg